



Detailed CFL Specification

PRODUCT CODE	DESCRIPTION	EAN	INNER BOX QTY	OUTER BOX QTY	WATTS	VOLTS	FREQUENCY	BASE	ENERGY CLASS	LUMENS	CRI	BEAM ANGLE	COLOUR TEMP IN KELVIN	POWER FACTOR	TIME TO 60% BRIGHTNESS	MERCURY CONTENT	AVERAGE LIFE IN HOURS	DIMMABLE NON DIMMABLE	SUITABLE FOR ACCENT LIGHTING ?	DIMENSIONS IN MM	SWITCHING CYCLES
HELIXT2/7W/SES27	ELECTRONIC SPIRAL 7W SES 2700K	5051203143051	25	100	7w	220v-240v	50/60hz	SES/E14	A	290	>80	360	2700K	0.55	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	84mm x 34mm	>8,000
HELIXT2/11W/BC27	ELECTRONIC SPIRAL 11W BC 2700K	5051203142429	25	100	11w	220v-240v	50/60hz	BC/B22	A	550	>80	360	2700K	0.57	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	93mm x 34mm	>8,000
HELIXT2/11W/ES27	ELECTRONIC SPIRAL 11W ES 2700K	5051203142849	25	100	11w	220v-240v	50/60hz	ES/E27	A	550	>80	360	2700K	0.57	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	93mm x 34mm	>8,000
HELIXT2/11W/SBC27	ELECTRONIC SPIRAL 11W SBC 2700K	5051203143587	25	100	11w	220v-240v	50/60hz	SBC/B15D	A	550	>80	360	2700K	0.57	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	93mm x 34mm	>8,000
HELIXT2/11W/SES27	ELECTRONIC SPIRAL 11W SES 2700K	5051203142818	25	100	11w	220v-240v	50/60hz	SES/E14	A	550	>80	360	2700K	0.57	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	93mm x 34mm	>8,000
HELIXT2/20W/BC27	ELECTRONIC SPIRAL 20W BC 2700K	5051203142511	25	100	20w	220v-240v	50/60hz	BC/B22	A	1150	>80	360	2700K	0.55	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	112mm x 44mm	>8,000
HELIXT2/25W/BC27	ELECTRONIC SPIRAL 25W BC 2700K	5051203142900	25	100	25w	220v-240v	50/60hz	BC/B22	A	1520	>80	360	2700K	0.56	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	118mm x 50mm	>8,000
HELIXT2/25W/ES27	ELECTRONIC SPIRAL 25W ES 2700K	5051203142931	25	100	25w	220v-240v	50/60hz	ES/E27	A	1520	>80	360	2700K	0.56	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	118mm x 50mm	>8,000
HELIX/30W/BC	ELECTRONIC SPIRAL 30W BC 2700K	5051203028600	25	50	30w	220v-240v	50/60hz	BC/B22	A	1900	>80	360	2700K	0.52	<10 Seconds	<1.2mg	10,000	NON DIMMABLE	NO	165mm x 60mm	>20,000
HELIX/30W/ES	ELECTRONIC SPIRAL 30W ES 2700K	5051203028624	25	50	30w	220v-240v	50/60hz	ES/E27	A	1900	>80	360	2700K	0.52	<10 Seconds	<1.2 mg	10,000	NON DIMMABLE	NO	165mm x 60mm	>20,000
HELIX/55W/BC27	ELECTRONIC SPIRAL 55W BC 2700K	5051203146052	5	25	55w	220v-240v	50/60hz	ES/E27	A	3150	>80	360	2700K	0.52	<40 Seconds	<5mg	8,000	NON DIMMABLE	NO	178mm x 75mm	>10,000
HELIX/55W/ES27	ELECTRONIC SPIRAL 55W ES 2700K	5051203146083	5	25	55w	220v-240v	50/60hz	BC/B22	A	3150	>80	360	2700K	0.52	<40 Seconds	<5mg	8,000	NON DIMMABLE	NO	178mm x 75mm	>10,000
HELIXT2/11W/SES64	ELECTRONIC SPIRAL 11W SES DAYLIGHT 6400K	5051203143174	25	100	11w	220v-240v	50/60hz	SES/E14	A	550	>80	360	2700K	0.57	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	93mm x 34mm	>8,000
HELIXT2/11W/BC64	ELECTRONIC SPIRAL 11W BC DAYLIGHT 6400K	5051203143358	25	100	11w	220v-240v	50/60hz	BC/B22	A	550	>80	360	2700K	0.57	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	93mm x 34mm	>8,000
HELIXT2/11W/ES64	ELECTRONIC SPIRAL 11W ES DAYLIGHT 6400K	5051203143143	25	100	11w	220v-240v	50/60hz	ES/E27	A	550	>80	360	2700K	0.57	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	93mm x 34mm	>8,000
HELIXT2/11W/SBC64	ELECTRONIC SPIRAL 11W SBC DAYLIGHT 6400K	5051203144898	25	100	11w	220v-240v	50/60hz	SBC/B15D	A	550	>80	360	2700K	0.57	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	93mm x 34mm	>8,000
HELIXT2/20W/ES64	ELECTRONIC SPIRAL 20W ES DAYLIGHT 6400K	5051203142993	25	100	20w	220v-240v	50/60hz	ES/E27	A	1150	>80	360	2700K	0.55	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	112mm x 44mm	>8,000
HELIX/30W/BC/640	ELECTRONIC SPIRAL 30W BC 6400K	5051203028617	25	50	30w	220v-240v	50/60hz	BC/B22	A	1900	>80	360	2700K	0.52	<10 Seconds	<1.2mg	10,000	NON DIMMABLE	NO	165mm x 60mm	>20,000
HELIX/30W/ES/640	ELECTRONIC SPIRAL 30W ES 6400K	5051203028631	25	50	30w	220v-240v	50/60hz	ES/E27	A	1900	>80	360	2700K	0.52	<10 Seconds	<1.2mg	10,000	NON DIMMABLE	NO	165mm x 60mm	>20,000
HELIX/55W/BC64	ELECTRONIC SPIRAL 55W BC 6400K	5051203146113	5	25	55w	220v-240v	50/60hz	BC/B22	A	3150	>80	360	2700K	0.52	<40 Seconds	<5mg	8,000	NON DIMMABLE	NO	178mm x 75mm	>10,000
HELIX/55W/ES64	ELECTRONIC SPIRAL 55W ES 6400K	5051203146144	5	25	55w	220v-240v	50/60hz	ES/E27	A	3150	>80	360	2700K	0.52	<40 Seconds	<5mg	8,000	NON DIMMABLE	NO	178mm x 75mm	>10,000
CEL/T2/7W/SBC/27	ELECTRONIC T2 CANDLE 7W SBC 2700K	5051203142757	25	100	7w	220v-240v	50/60hz	SBC/B15D	A	290	>80	360	2700K	0.55	<40 Seconds	<1mg	8,000	NON DIMMABLE	NO	102mm x 37mm	>8,000
CEL/T2/7W/ES/27	ELECTRONIC T2 CANDLE 7W ES 2700K	5051203143204	25	100	7w	220v-240v	50/60hz	ES/E27	A	290	>80	360	2700K	0.55	<40 Seconds	<1mg	8,000	NON DIMMABLE	NO	102mm x 37mm	>8,000
CEL/T2/9W/BC/27	ELECTRONIC T2 CANDLE 9W BC 2700K	5051203142603	25	100	9w	220v-240v	50/60hz	BC/B22	A	405	>80	360	2700K	0.59	<40 Seconds	<1mg	8,000	NON DIMMABLE	NO	102mm x 37mm	>8,000
CEL/T2/9W/ES/27	ELECTRONIC T2 CANDLE 9W ES 2700K	5051203143617	25	100	9w	220v-240v	50/60hz	ES/E27	A	405	>80	360	2700K	0.59	<40 Seconds	<1mg	8,000	NON DIMMABLE	NO	102mm x 37mm	>8,000
CEL/T2/9W/SBC/27	ELECTRONIC T2 CANDLE 9W SBC 2700K	5051203143556	25	100	9w	220v-240v	50/60hz	SBC/B15D	A	405	>80	360	2700K	0.59	<40 Seconds	<1mg	8,000	NON DIMMABLE	NO	102mm x 37mm	>8,000
CEL/T2/11W/SBC/27	CEL T2 11W SBC 2700K MICRO CANDLE	5051203142696	20	100	11w	220v-240v	50/60hz	SBC/B15D	A	530	>81	360	2700K	0.55	<40 Seconds	<1mg	8,000	NON DIMMABLE	NO	113mm x 38mm	>8,000
GLS/MICRO/11W/BC	GLS 11W BC MICRO 2700K	5051203123657	25	100	11w	220v-240v	50/60hz	BC/B22	A	535	>80	360	2700K	0.55	<60 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	55mm x 103mm	>8,000
HELIX/25W/BC/BLB	ELECTRONIC SPIRAL 25W BC BLACKLIGHT U.V	5051203146748	25	100	25w	220v-240v	50/60hz	BC/B22	A	N/A	>80	360	N/A	0.55	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	152mm x 60mm	>8,000
HELIX/25W/ES/BLB	ELECTRONIC SPIRAL 25W ES BLACKLIGHT U.V	5051203147356	25	100	25w	220v-240v	50/60hz	ES/E27	A	N/A	>80	360	N/A	0.55	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	152mm x 60mm	>8,000
ELT/15W/BC/SENS	3 TURN 240V 15W B22d 2700K SENSOR	5051203014764	25	100	15w	220v-240v	50/60hz	BC/B22	A	815	>80	360	2700K	0.55	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	56.5mm x 28.3mm x 20.2mm	>8,000
ELT/15W/ES/SENS	3 TURN 240V 15W E27 2700K SENSOR	5051203014795	25	100	15w	220v-240v	50/60hz	ES/E27	A	815	>80	360	2700K	0.55	<30 Seconds	<2.3mg	8,000	NON DIMMABLE	NO	56.5mm x 28.3mm x 20.2mm	>8,000